

DS-2CE56D0T-VFIR3E 2MP PoC Manual Varifocal Turret Camera



- 2 MP varifocal PoC turret camera
- 2.8 mm to 12 mm varifocal lens
- Up to 40 m IR distance for bright night imaging
- Water and dust resistant (IP67)
- Transmits both HD video and power over the same coaxial cable

▪ Specification






Camera	
Image Sensor	2 MP progressive scan CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F1.4, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	Varifocal lens, manual adjustment, 2.8 mm to 12 mm
Focal Length & FOV	Horizontal FOV 105.2° to 32.8°
Lens Mount	Φ14
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 40 m
Image	
Image Settings	Brightness,Mirror,Sharpness,AGC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Image Enhancement	DWDR,BLC
Noise Reduction	2D DNR
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ±15%/PoC.at, max. 6.5 W
Material	Main body: Metal, Enclosure: Plastic
Dimension	∅ 130.5 mm × 102.4 mm (∅ 5.14" × 4.03")
Weight	Approx. 710 g (1.57 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity 90% or less (non-condensation)
Language	English
Approval	
Protection	IP67

▪ Available Model

DS-2CE56D0T-VFIR3E(2.8-12mm)

▪ **Accessory**

▪ **Optional**

DS-1275ZJ-SUS(Grey)#UK	DS-1281ZJ-M Inclined Ceiling Mount	DS-1280ZJ-M Junction Box	DS-1276ZJ-SUS Corner Mount	DS-1275ZJ-SUS Vertical Pole Mount
				
DS-1271ZJ-130-TRL Pendant Mount	DS-1273ZJ-130-TRL Wall Mount			
				

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

